







































































3FM1.2 6V 1.2Ah					
3FM4 6V 4.0Ah					
3FM10 6V 10Ah					
6FM0.8 12V 0.8Ah					
6FM1.2 12V 1.2Ah					
6FM2 12V 2.0Ah					
6FM2S 12V 2.0Ah					
6FM3 12V 3.0Ah					
6FM7 12V 7.0Ah					
6FM12 12V 12Ah					
6FM18 12V 18Ah					
6FM26 12V 26Ah					
6FM38 12V 38Ah					
6FM50 12V 50Ah					



FEATURES:

- ▶ Maintenance Free
- ▶ High Power Density
- ▶ No Memory Effect
- ▶ Low Self Discharge
- ▶ Long Service Life
- ▶ Wide Operating Temp. Range
- ▶ Wide Ranging Applications

PHYSICAL SPECIFICATIONS

Model No.	Nominal Voltage	Capacity (20HR)	Dimensions (mm)				Weight (Approx)	Internal Resistance Fully charged battery
			Length	Width	Height	Total Height		
3FM1.2	6V	1.2AH	97	24	51.5	57.5	0.28kg	
3FM4	6V	4AH	70	47	100	105	0.81kg	
3FM10	6V	10AH	151	51	94	100	1.9kg	
6FM0.8	12V	0.8AH	96	25	62	62	0.34kg	
6FM1.2	12V	1.2AH	97	43	52	58	0.6kg	
6FM2	12V	2AH	178	35	60	66	1.0kg	
6FM2S	12V	2AH	70	47	99	103	1.0kg	
6FM3	12V	3.0AH	134	67	60.5	66.5	1.32kg	20°C, 68°F, 50mΩ
6FM7	12V	7AH	151	65	94	100	2.54kg	
6FM12	12V	12AH	151	98	95	101	3.85kg	
6FM18	12V	18AH	181.5	77	167.5	167.5	5.7kg	
6FM26	12V	26AH	176	166.5	125	125	8.2kg	
6FM38	12V	38AH	197	165	170	170	13.8kg	
6FM50	12V	50AH	257	132	200	200	17.0kg	-----

ELECTRICAL SPECIFICATIONS

Model No.	Rate Capacity									
	20 Hour Rate		10 Hour Rate		5 Hour Rate		1 Hour Rate		15 Minute Rate	
3FM1.2	70mA	1.4AH	130mA	1.3AH	240mA	1.2AH	850mA	0.85AH	2.6A	0.65AH
3FM4	231mA	4.6AH	410mA	4.1AH	740mA	3.7AH	2.85A	2.85AH	9.02A	2.25AH
3FM10	525mA	10.5AH	980mA	9.8AH	1.87A	9.35AH	6.82A	6.82AH	21.56A	5.39AH
6FM0.8	40mA	0.8AH	72mA	0.72AH	140mA	0.7AH	500mA	0.5AH	1.57A	0.39AH
6FM1.2	70mA	1.4AH	130mA	1.3AH	240mA	1.2AH	850mA	0.85AH	2.6A	0.65AH
6FM2	105mA	2.1AH	190mA	1.9AH	360mA	1.8AH	1.3A	1.3AH	4.12A	1.03AH
6FM2S	102mA	2.0AH	180mA	1.8AH	350mA	1.8AH	1.2A	1.2AH	4.0A	1.0AH
6FM3	176mA	3.5AH	330mA	3.3AH	600mA	3.0AH	2.17A	2.17AH	6.86A	1.71AH
6FM7	350mA	7AH	630mA	6.3AH	1.19AH	5.5AH	4.34A	4.34AH	13.72A	3.43AH
6FM12	600mA	12AH	1.1A	11.1AH	2.07A	10.7AH	7.24A	7.24AH	22.3A	5.6AH
6FM18	900mA	18AH	1.7A	17AH	3.2A	16AH	11.1A	11.1AH	34.3A	8.6AH
6FM26	1.3A	26AH	2.4A	24AH	4.42A	21.6AH	16.1A	16.1AH	50.9A	12.7AH

Model No.	Rate Capacity									
	20 Hour Rate		10 Hour Rate		5 Hour Rate		3 Hour Rate		1 Hour Rate	
6FM38	2.0A	40AH	3.8A	38AH	6.7A	33.5AH	10.1A	30.3AH	24.3A	23.4AH
6FM50	2.75A	55AH	5.1A	51AH	8.8A	44AH	13.3A	39.9AH	30.6A	30.6AH